

Hillrom P1600 Advanta Refurbished



Product Description

The Advanta Med Surg Bed offers improved ease of use through innovation and proven performance. Designed to help caregivers accomplish their goals, the Advanta Med Surg Bed provides patients egress/ingress, less patient positioning, and more convenience through storage and other features.

Features

- Smart Bed technology enabled for connectivity with NaviCare® Nurse Call, other nurse call systems and EMRs.
- SafeView® alerts system
- Bed exit monitoring system with Hill-Rom's patented three-level detection algorithms
- Nightlight
- Audible "brake not set" alarm
- SlideGuard® bed articulation technology with Auto Contour™ feature

Hillrom P1600 Advanta Refurbished

- Electric vascular foot position
- Care Grip patient egress assist handle
- Point-of-Care® nurse controls
- One-button Dining Chair® feature
- IntelliDrive® powered transport or central 5th steering wheel
- Automatic battery backup
- Digital head of bed angle display
- 30° head of bed alarm
- Sidecom® nurse call and entertainment controls
- One-hand bed extender
- Integrated Line Manager
- Positioning controls accessible to the patient
- Bed articulations

Specification

- Total Length 91" (231 cm)
- Retracted Length 78.5" (199.4 cm)
- Mattress Support Width 35" (89 cm)
- Mattress Support Length 83" (211 cm)
- Maximum Width (siderails up) 42.75" (108.59 cm)
- Maximum Width (siderails stored) 36" (91 cm)
- Maximum Headboard Height 18" (122 cm)
- Maximum Footboard Height 45" (114 cm)
- Maximum Siderail Height 45" (114 cm)
- Power Cord Length (minimum) 72" (183 cm)
- Bed Clearance 4.75" (12.07 cm)
- Wheel Base – Length 47.88" (121.62 cm)
- Wheel Base – Width 24.75" (62.87 cm)
- Head Section Inclination (maximum) 65°
- Knee Section Inclination (maximum) 35°
- Automatic Contour Up (maximum) 15°
- Automatic Contour Down 28°
- Automatic Contour 10°
- Hilow Range 13.25" (33.66 cm)
- Trendelenburg 11°
- Reverse Trendelenburg 11°
- Caster Minimum Diameter 5" (13 cm)
- Caster Minimum Tread Width 31/32" (24.60 mm)
- Caster Minimum Stem Diameter 1" (3 cm)
- Weight Capacity: 500 Lbs.